



PENNSYLVANIA LUMBERMENS MUTUAL
INSURANCE COMPANY

SAWMILL SAFETY INSPECTION

Date: _____

Inspected By: _____

PART I

LOG YARD AND DECK	YES	NO	CORRECTION DATE
Approved hard hats worn by all persons			
Safety boots worn by all persons			
Hand protection/gloves worn where needed			
All yard equipment maintained for safe operation			
Log yard storage areas maintained orderly			
Log deck equipped with stops, chains or other safeguards to prevent logs from rolling down			
All belts, pulleys, rotating shafts, chains, sprockets and gears properly guarded			
Area around debarker and conveyors guarded to prevent access by unauthorized personnel			
Debarker operator protected by panel of safety glass and wears appropriate personal protective equipment			
Buck saw guarded by a barrier guard, railings or other suitable means			
Eye protection worn			
Hearing protection worn where needed			

PART II

SAWMILL AREA	YES	NO	CORRECTION DATE
Approved hard hats worn by all persons			
Safety boots worn by all persons			
Hand protection/gloves worn where needed			
Eye protection worn where needed			
Hearing protection worn where needed			
All belts, pulleys, rotating shafts, chains, sprockets and gears properly guarded			
All electrical motors and hand tools grounded			
All electrical wires maintained			

SAWMILL AREA	YES	NO	CORRECTION DATE
All electrical junction boxes, outlets and switches maintained in good condition			
All electrical breaker switches identified as to their use			
LO/TO used when repairs made			
All side-hinged doors leading to outside are marked as "Exit"			
All abrasive wheel grinders grounded			
Abrasive wheel grinder anchored to table			
Abrasive wheel grinder equipped with work rest, side shield and tongue guard			
Have work rest adjusted to 1/8" and tongue guard to 1/4"			
All oxygen and acetylene secured			
Oxygen and acetylene secured with valve protection caps			
Oxygen and acetylene separated by 20' when stored			
Oxygen and acetylene have all gauges in good condition			
Use special wrench on cylinders when required			
Hoses on cylinders in good condition			
Fire extinguisher located within 50' travel distance			
Fire extinguishers fully charged			
Annual inspection on fire extinguishers			
Fire extinguishers not blocked and accessible			
All floors, aisles and passageways clean, dry and unobstructed			
All overhead storage area floors marked with capacity			
All stairways having four or more risers equipped with stair rails or handrails			
All ladders in good condition (no broken rungs or split rails)			
Mechanical ventilation provided when welding or cutting if workers exposed to hazardous chemicals			
Air compressors maintained			
Air compressors have relief valve and gauge operating			
Air compressors have pulleys and belts guarded			
All overhead hoists legibly marked with rated load weight			

PART III

SAWMILL EQUIPMENT	YES	NO	CORRECTION DATE
Log carrier runway equipped with bumpers, and travel either barricaded or signs posted to keep out unauthorized personnel			
Head saw operator protected from flying debris			
Anti-kickback device installed on back of edger blades			
All saws and pressure-feed rolls guarded against accidental contact			
Chippers and hogs guarded to prevent contact with cutting blades			
Lumber stacked properly to prevent falling			

PART IV

GENERAL	YES	NO	CORRECTION DATE
Recordkeeping: OSHA poster			
OSHA Form 301 and 300 log maintained			
Material Safety Data Sheets maintained			
Adequate first aid supplies available			
Emergency telephone numbers posted			
Fuel dispensing areas maintained			
No smoking signs posted around tanks			
Vehicle barrier around tanks			
Contents of tanks labeled			
Approved fire extinguisher kept near tanks			

RECOMMENDATIONS
